



SERIE T/i



T/9i

REL have a longstanding tradition of requiring the top model in any range to be more. More than the sum of its parts, it represents the grandest scale, the highest output and the most we can do within any given technology envelope.

T/9i, THE MOST T/i: T/9i represents the most of T/i that we can deliver, and if sheer output alone is a primary requirement for your theater or music system then read no further. The combination of a lightweight, composite FibreAlloy™ 10" driver coupled to a matching 10" T/i passive delivers speed, slam and attack when called upon but also is capable of tracing more delicate passages when necessary. Large in sonic scale, the T/9i is ideal for mating up with floor standing speakers and rooms that are on the medium-to-large size. Powerful, concussive, yet beautiful.

T/9i delivers more than just raw output. We started with our driver upgrades and built outward. The lovely cabinets grew by 4 lbs. (1.8 kg) over its predecessor due to thicker cabinet walls and improved bracing. Why? Because the additional speed and impact of the new drivers requires greater control or the benefits can be lost before they get to the listener.

GREAT SUBS, GREAT AMPS:

REL's acclaimed input filters and robust amplifiers, for T/9i a powerful 300w Class A/B design, result in the best sounding, most reliable designs ever produced. High current power supplies, huge toroidal transformers, and what many critics call the best filters in the world produce the famous REL Effect—wherein not simply the bass region but ALL music and movie sound is uplifted and improved.



REL PREFER TO REFINE, to build generationally upon a solid foundation while searching relentlessly for every possible way to legitimately improve upon our past performance. With T/i, we believe we have set a new standard for overall performance in this price category.



Arrow™ is REL's latest generation of zero compression wireless. Super-fast delivery of both High Level Bass and .1/ LFE ensures the rich, natural warmth only RELs can deliver.



T/9i

REL have a longstanding tradition of requiring the top model in any range to be more. More than the sum of its parts, it represents the grandest scale, the highest output and the most we can do within any given technology envelope.

T/9i, THE MOST T/i: T/9i represents the most of T/i that we can deliver, and if sheer output alone is a primary requirement for your theater or music system then read no further. The combination of a lightweight, composite FibreAlloy™ 10" driver coupled to a matching 10" T/i passive delivers speed, slam and attack when called upon but also is capable of tracing more delicate passages when necessary. Large in sonic scale, the T/9i is ideal for mating up with floor standing speakers and rooms that are on the medium-to-large size. Powerful, concussive, yet beautiful.

T/9i delivers more than just raw output. We started with our driver upgrades and built outward. The lovely cabinets grew by 4 lbs. (1.8 kg) over its predecessor due to thicker cabinet walls and improved bracing. Why? Because the additional speed and impact of the new drivers requires greater control or the benefits can be lost before they get to the listener.

GREAT SUBS, GREAT AMPS: REL's acclaimed input filters and robust amplifiers, for T/9i a powerful 300w Class A/B design, result in the best sounding, most reliable designs ever produced. High current power supplies, huge toroidal transformers, and what many critics call the best filters in the world produce the famous REL Effect—wherein not simply the bass region but ALL music and movie sound is uplifted and improved.



T/7i

T/7i is, without reservation, one of the best-balanced RELs of all time. In order to achieve perfect balance, a sub must weigh speed against heft, while ensuring true extension-depth-and do so in a physically harmonious package. T/7i manages to make it all seem easy. Quick and delicate for a perfect blend, it can pound out exceptionally deep, tuneful bass that belies its size and plays louder than most will ever require.

GOING FASTER REQUIRES A BETTER ENGINE: The new composite FibreAlloy™ 8" bass engine in T/7i blends precisely the correct dimension of stiffening alloy with a fibre material chosen for its sonic neutrality and light weight. The combination is brilliant; exceeding the performance of competitors' drivers that are many times more expensive. The forward-firing 8" active couples with a larger 10" down-firing passive, again with carefully chosen balances of alloy to fibre and the result is seamless, effortlessly deep bass that blends perfectly with one's main speakers.

ELECTRONICS, THE POWER BEHIND THE BRAND: If our driver designers deliver the structure of REL's sound, the electronics are the power behind our success. T/7i uses a 200w Class A/B design with large, high current power supplies, precision-wound toroidal transformers and an amazing reliability record that has powered almost 100,000 RELS in the T-range over the years.



T/5i

SIMPLIFY, THEN ADD LIGHTNESS: Simplicity is its own reward and T/5i reduces the classic cubic sub to its bare essence. Just a single, high quality FibreAlloy™ composite driver, down firing to produce maximum coupling with the floor eliminates the need for a grille; T/5i is the purest expression of REL.

We began by updating our classic 8" bass engine to reduce mass, while greatly increasing stiffness. This improvement led to upgrading cabinet dimensions and wall thickness to better control the deep bass. Additional upgrades extended even into the design of our feet, resulting in greater speed and solidity to the presentation of sound.

REL's electronics are the brains and power behind our success. Serie T/i uses the same Class A/B power amplifier sections with large, high current power supplies, precision-wound transformers and an amazing reliability record that has powered some 100,000 RELs.

BEAUTY AND BRAWN: T/5i is powered by a rich sounding 125w Class A/B amplifier that cuts no corners. Over-specified mains transformers, discrete output devices, high current power supplies; T/5i shares all the DNA and quality construction of its larger, more powerful brethren but is simply scaled down in output, not quality and retains the legendary reliability REL have become know for the world over.



T/5i

T/7i

T/9i

**T/9i SPECIFICATIONS****T/7i SPECIFICATIONS****T/5i SPECIFICATIONS**

Type	Passive Radiator, front-firing active woofer, down-firing passive radiator	Passive Radiator, front-firing active woofer, down-firing passive radiator	Closed Box, down-firing active woofer
Active Drive Unit	10in. (254 mm) long-throw, inverted dust cap, steel chassis	8in. (200 mm) long-throw, inverted dust cap, steel chassis	8in. (200 mm) long-throw, inverted dust cap, steel chassis
Passive Radiator	10in. (254 mm)	10in. (254 mm)	N/A
Lower Frequency Response	28 Hz at -6 dB in room	30 Hz at -6 dB in room	32 Hz at -6 dB in room
Input Connectors	Hi Level Neutrik Speakon, Lo Level single phono, LFE phono	Hi Level Neutrik Speakon, Lo Level single phono, LFE phono	Hi Level Neutrik Speakon, Lo Level single phono, LFE phono
Input Impedance	High Level: 150k, Low Level: 10k, .1/LFE: 10k ohms	High Level: 150k, Low Level: 10k, .1/LFE: 10k ohms	High Level: 150k, Low Level: 10k, .1/LFE: 10k ohms
Gain Control Range	80 dB	80 dB	80 dB
Power Output	300 Watts (RMS)	200 Watts (RMS)	125 Watts (RMS)
Phase Switch	Yes, 0 or 180 degrees	Yes, 0 or 180 degrees	Yes, 0 or 180 degrees
Amplifier Type	Class AB	Class AB	Class AB

Protection System

Fully Electronic SET-SAFE	Yes	Yes	Yes
D.C. Fault	Yes	Yes	Yes
Output Short	Yes	Yes	Yes
Mains Input Voltage	220-240 volts, 110-120 volts for certain markets	220-240 volts, 110-120 volts for certain markets	220-240 volts, 110-120 volts for certain markets
Fuses	3.15 Amp semi delay 230 volts operation, 6.3 Amp semi delay 115 volts operation	2 Amp semi delay 230 volts operation, 4 Amp semi delay 115 volts operation	1.6 Amp semi delay 230 volts operation, 3.15 Amp semi delay 115 volts operation

Dimensions & Finish

Dimensions (WHD)	13 x 15.2 x 16 in., (330 x 387 x 407 mm) Including Feet and Rear Panel Controls Add 1.75 in (44.5 mm) in depth when using Hi Level connector	12 x 14.3 x 15 in., (305 x 362 x 382 mm) Including Feet and Rear Panel Controls Add 1.75 in (44.5 mm) in depth when using Hi Level connector	10.5 x 12.5 x 12.7 in., (267 x 317 x 322 mm) Including Feet and Rear Panel Controls Add 1.75 in (44.5 mm) in depth when using Hi Level connector
Net Weight	41.3 lbs. (18.7 kg)	36 lbs. (16.3 kg)	26.5 lbs. (12 kg)
Finish	Gloss Piano Black or White Lacquer	Gloss Piano Black or White Lacquer	Gloss Piano Black or White Lacquer

Supplied Accessories

Mains Lead	Yes	Yes	Yes
Neutrik Speakon Interconnect	Yes (10 Meters Nominal)	Yes (10 Meters Nominal)	Yes (10 Meters Nominal)
Users Manual	Yes	Yes	Yes

In the interest of product development, REL Acoustics Limited reserves the right to vary these specifications without notice.

Join the Pursuit™
rel.net